



Total Solution Provider in Saw Device

SA1370AM

Wireless, RF SAW Filter
Revision 0: February 2009



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com



Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.3

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	1370.0	-
Insertion Loss within 1350.0 ~ 1390.0 MHz	dB	-	1.7	3.5
Amplitude Ripple within 1350.0 ~ 1390.0 MHz	dB _{p-p}	-	0.8	1.5
Attenuation:				
1260.0 ~ 1300.0 MHz	dB	33	37	-
1440.0 ~ 1480.0 MHz	dB	32	35	-
VSWR within 1350.0~1390.0 MHz	-	-	1.8	2.5

Notes : (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


Package Dimensions



Marking Descriptions	
Y	Wireless Application
j	Series Number
a	Date Code(Year)
b	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In or Out
B	Out or In



Testing Environment



Source & Load Impedance: 50 Ω



□ Frequency Characteristics

Frequency Response





VSWR



Smith Chart

