



Total Solution Provider in Saw Device

SA1887AM1

Wireless, RF SAW Filter
Revision 0:



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com

□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-20	-	+70
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	3
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M1			
Length x Width	-	-	3.0 x 3.0	-
Height	mm	-	-	1.3

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	1887.5	-
Insertion Loss within 1886.5 ~ 1888.5 MHz	dB	-	1.1	1.5
Amplitude Ripple within 1886.5 ~1888.5 MHz	dB _{p-p}	-	0.02	0.4
Attenuation:				
D.C. ~ Fo-70.0 MHz	dB	20	22	-
Fo+70.0 ~ 3000.0 MHz	dB	20	25	-

Notes : (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


□ Package Dimensions



Marking Descriptions	
V	Wireless Application
s	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, E, G	Ground
B	In
F	Out

□ Testing Environment



Source & Load Impedance: 50 Ω

□ Frequency Characteristics

Frequency Response

