



*Total Solution Provider in Saw Device*

---

# SA1970CM

Wireless, RF SAW Filter  
Revision 0: September 2007



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

---

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


| Parameters Description                         | Unit            | Minimum | Typical   | Maximum |
|--|-----------------|---------|-----------|---------|
| Operating Temperature Range                    | °C              | -30     | -         | +80     |
| Storage Temperature Range                      | °C              | -40     | -         | +85     |
| Maximum DC Voltage                             | V               | -       | -         | 3       |
| Maximum Input Power                            | dBm             | -       | -         | 10      |
| Source Impedance (single ended) <sup>(1)</sup> | Ω               | -       | 50        | -       |
| Load Impedance (single ended) <sup>(1)</sup>   | Ω               | -       | 50        | -       |
| Package type & size                            | M               |         |           |         |
| Length x Width                                 | mm <sup>2</sup> | -       | 3.0 x 3.0 | -       |
| Height   | mm              | -       | -         | 1.3     |

### Electrical Specification

| Parameters Description                      | Unit              | Minimum | Typical | Maximum |
|---|-------------------|---------|---------|---------|
| Center Frequency (Fo)                       | MHz               | -       | 1970.0  | -       |
| Insertion Loss within 1960.0 ~ 1980.0 MHz   | dB                | -       | 2.2     | 3.0     |
| Amplitude Ripple within 1960.0 ~ 1980.0 MHz | dB <sub>p-p</sub> | -       | 0.8     | 1.5     |
| Return Loss within 1960.0 ~ 1980.0 MHz      | dB                | 9       | 12      | -       |
| <b>Attenuation:</b>                         |                   |         |         |         |
| 1900.0 MHz                                  | dB                | 20      | 30      | -       |

**Notes :** (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


**Package Dimensions**



| Marking Descriptions |                      |
|----------------------|----------------------|
| V                    | Wireless Application |
| z                    | Series Number        |
| X                    | Date Code(Year)      |
| Y                    | Date Code(Month)     |

| Pin Description |        |
|-----------------|--------|
| A, C, D, F      | Ground |
| E               | In     |
| B               | Out    |


**Testing Environment**



Source & Load Impedance: 50 Ω

## □ Frequency Characteristics

Frequency Response



Return Loss

