



*Total Solution Provider in Saw Device*

---

# SA815AM

PTT, RF SAW Filter  
Revision 1: January 2010



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

---

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+70
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	20
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	M			
Length x Width	mm <sup>2</sup>	-	3.0 x 3.0	-
Height	mm	-	-	1.3

### Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	813.5	-
Insertion Loss within 806 ~ 821 MHz	dB	-	2.2	3.0
Group delay ripple within 806 ~ 821 MHz	ns <sub>p-p</sub>	-	15	30
<b>Attenuation:</b>				
851.0 ~ 866.0 MHz	dB	40	50	-
935.0 ~ 940.0 MHz	dB	35	40	-
960.65 ~ 979.65 MHz	dB	35	41	-
1115.30 ~ 1134.30 MHz	dB	37	42	-
1269.95 ~ 1288.95 MHz	dB	40	51	-
1612.0 ~ 1650.0 MHz	dB	35	43	-
1650.0 ~ 2600.0 MHz	dB	25	30	-
VSWR within 806 ~ 821 MHz	-	-	1.7	2.0

**Notes :** No Matching Network (Ref. Testing Environment Circuit as shown below).


**Package Dimensions**



Marking Descriptions	
N	PTT Application
5	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In or Out
B	Out or In



**Testing Environment**





Source & Load Impedance: 50 Ω

**□ Frequency Characteristics**

Frequency Response



### VSWR



### Smith Chart

