



*Total Solution Provider in Saw Device*

---

# SA861AM

iDEN, RF-Rx SAW Filter  
Revision 0: October 2003



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

---

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+70
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	15
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	M			
Length x Width	mm <sup>2</sup>	-	3.0 x 3.0	-
Height	mm	-	-	1.3

### Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	861.0	-
Insertion Loss within 851 ~ 871 MHz	dB	-	2.5	3.5
Amplitude Ripple within 851 ~ 871 MHz	dB <sub>p-p</sub>	-	0.6	1.5
<b>Attenuation:</b>				
D.C. ~ 806 MHz	dB	27	49	-
806 ~ 825 MHz	dB	37	50	-
896 ~ 902 MHz	dB	28	34	-
905.825 ~ 924.825 MHz	dB	27	39	-
960 ~ 979 MHz	dB	37	53	-
1070 ~ 1089 MHz	dB	47	51	-
1089 ~ 3000 MHz	dB	27	32	-
VSWR within 851 ~ 871 MHz	-	-	1.6	2.0

**Notes :** (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


**Package Dimensions**



Marking Descriptions	
L	CDMA450 Application
R	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



**Testing Environment**





Source & Load Impedance: 50 Ω

**□ Frequency Characteristics**

Frequency Response



### VSWR



### Smith Chart

