



Total Solution Provider in Saw Device

SA881DM

CDMA , RF-Rx SAW Filter
Revision 0:



- Electrical Characteristics
 - Package Dimensions
 - Testing Environment
 - Frequency Characteristics
-

SAWNICS Inc.

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / www.sawnics.com

□ Electrical Characteristics

Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+80
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	15
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.3

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	881.5	-
Insertion Loss within 869~894MHz	dB	-	2.2	3.0
Amplitude Ripple within 869~894MHz	dB _{p-p}	-	0.6	1.5
Attenuation:				
D.C. ~ 779 MHz	dB	50	60	-
779 ~ 849 MHz	dB	42	47	-
914 ~ 970 MHz	dB	26	30	-
970 ~ 1049 MHz	dB	50	58	-
1049 ~ 2000 MHz	dB	45	55	-
VSWR within 869~894MHz	-	-	1.6	2.0

Notes : (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


□ Package Dimensions



Marking Descriptions	
B	CDMA800 Application
2	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



□ Testing Environment





Source & Load Impedance: 50 Ω

Frequency Characteristics

Frequency Response



VSWR



Smith Chart

