



*Total Solution Provider in Saw Device*

---

# SA902BM

GSM, RF SAW Filter

Revision 0:



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

---

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-25	-	+75
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	M			
Length x Width	mm <sup>2</sup>	-	3.0 x 3.0	-
Height	mm	-	-	1.3

### Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	902.5	-
Insertion Loss (890~915 MHz)	dB	-	3.0	3.5
Amplitude Ripple within 890~915 MHz	dB <sub>p-p</sub>	-	0.8	1.5
<b>Attenuation:</b>				
D.C. ~ 845 MHz	dB	48	52	-
845 ~ 870 MHz	dB	40	45	-
925 ~ 935 MHz	dB	5	15	-
935 ~ 980 MHz	dB	25	32	-
980 ~ 1200 MHz	dB	45	49	-
1200 ~ 3000 MHz	dB	25	38	-
VSWR (890~915 MHz)	-	-	1.8	2.3

**Notes :** (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


**Package Dimensions**



Marking Descriptions	
C	GSM Application
1	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



**Testing Environment**





Source & Load Impedance: 50 Ω

**□ Frequency Characteristics**

Frequency Response



**VSWR**



**Smith Chart**

