



*Total Solution Provider in Saw Device*

---

# SA911AM

RFID, RF SAW Filter  
Revision 0: July 2005



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

---

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+65
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	20
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	M			
Length x Width	mm <sup>2</sup>	-	3.0 x 3.0	-
Height	mm	-	-	1.3

### Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	911.0	-
Insertion Loss within 908.0 ~ 914.0 MHz	dB	-	2.7	3.5
Amplitude Ripple within 908.0 ~ 914.0 MHz	dB <sub>p-p</sub>	-	0.3	1.0
<b>Attenuation:</b>				
D.C. ~ 845.0 MHz	dB	48	54	-
894.0 MHz	dB	45	49	-
960.0 ~ 1200.0 MHz	dB	47	52	-
1200.0 ~ 2000.0 MHz	dB	35	42	-
VSWR within 908.0 ~ 914.0 MHz	-	-	1.55	2.0

**Notes :** (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


**Package Dimensions**



Marking Descriptions	
L	Wireless Application
V	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



**Testing Environment**





Source & Load Impedance: 50 Ω

## □ Frequency Characteristics

Frequency Response



### VSWR



### Smith Chart

